



AT A GLANCE

Real 15000Watt RMS power capacity (8 hours pink noise)

Premium 18" LF drivers with massive ±15mm linear Xmax

Triple forced cooling system for low power compression

Heavily braced cabinet for vibration free dynamic response

Touring grade textured black paint finish

APPLICATIONS

BFX118S subwoofers are suitable for bass reinforcement on main PA systems, touring or permanent installations for small to large stages, indoor or outdoor live performances.

- FOH
- Multi-functional rooms
- Auditorium and Theatre
- Night Clubs

SPECIFICATIONS

Power handling (50~15000Hz pink noise 8 hours) 1500W RMS

Nominal impedance 8 Ohm

Manufacturing Consistency tolerance ±6dB from 30 to 1000Hz

Calculated Maximum SPL / 1m 132dB continuous / 135dB Program

Nominal Directivity (-6dB) Omni in useable band

Recommended filters 30Hz 24dB/Oct HPF 80-120Hz LPF

Low Frequency driver Custom made 1x18" 4.5" In/Out Voice coil

Crossover No-active Mode external DSP only

Flying hardware No-Ground stack only

Connectors 2x NEUTRIK Speakon® NL4MP

Floor monitor use No

Pole Mount Yes 35mm

Cabinet CNC made with tongue and grove assembly 25 and 18mm birch plywood

Finish Touring grade black textured coating

Size (WxHxD) 563x590x692mm

Weight 43kg net, 47kg gross