



BK15

Harmony Series



AT A GLANCE

- Real 400W RMS power capacity (8 hours pink noise)
- Natural sound and Flat reproduction
- Optimized for smooth frequency response in and out axis
- Premium Neodymium custom made European Drivers
- 80°x50° rotatable horn
- Heavy braced birch plywood cabinet (15 mm)
- Touring grade soft touch black painting

APPLICATIONS

- Bk15 speakers are suitable for near field main PA reinforcement with or without subwoofers
 Portable system or permanent installation, monitor on stages, and delay fill.
 Suitable in spaces like:
- FoH
 - Multi-functional room
 - Auditorium and Theater
 - Nightclub
 - Pub
 - Bar
 - Commercial announcements

SPECIFICATIONS

Power handling (50~15000Hz pink noise 8 hours)	400W RMS 800W Program
Nominal impedance	8 Ohm
Manufacturing Consistency tolerance	±1.5dB from 300 to 10000Hz
Average Sensitivity (wideband 200~16000Hz)	98db 1watt 1 meter
Calculated Maximum SPL / 1m	124dB continuous / 127dB Program
Nominal Directivity (-6dB)	80° x 50° above 1200Hz Rotatable
Recommended low cut filter	40Hz 24dB/Oct in full range mode 50-120Hz with subwoofer
Low Frequency driver	Custom made 1x15" ferrite magnet, 3" In/Out Voice coil
High Frequency driver	Custom made 1x 1inch ferrite magnet 1.7" Voice coil
Crossover	Passive mode only 1800Hz, 12dB/oct on LF and 18/oct HF
Flying hardware	8 M8 flying points
Connectors	2x NEUTRIK Speakon® NL4MP (1+/1- Input, 2+/2- link)
Floor monitor use	yes
Pole Mount	35mm pole mount
Cabinet	CNC made with tongue and groove assembly 25 and 18mm birch plywood
Finish	Touring grade black rubberized textured coating
Size (WxHxD)	445 x 710 x 414 mm
Weight	26kg net, 29kg gross